

LED Lighting Surge Protector Datasheet

ZYS-P10A(3 Wires)



Overview

ZYS-P10A series surge protector is a transient over-voltage protection device specially used for outdoor LED lighting system. It is mainly composed of thermal protection varistor and gas discharge tube device. It can be installed in LED lamp or perpetual lamp and connected with LED power driver to provide reliable surge protection. It can effectively prolong the service life of lamps and improve the stability of lamps and lanterns. The protection device must be metal oxide varistor type MOV (Metal Oxide Varistor).

Agency Approvals

Agency	Standard	Agency File Number
	UL1449	E502491
	EN61643-11:2012+A II	J50532068

Features

- ◆ Applicable to class I or II lamps
- ◆ Built in protection mode: L-N, L-PE, N-PE
- ◆ Built in thermal separation function for higher security
- ◆ Parallel isolation design, excellent protection performance
- ◆ Excellent surge resistance and very low residual voltage
- ◆ UL 1015 16#Electronic wire
- ◆ Small and convenient for embedded installation
- ◆ IP65 dust proof and waterproof grade

Application

- ◆ Digital Signage
- ◆ Traffic Lighting
- ◆ Flood Lighting
- ◆ Tunnel Lighting
- ◆ Street lighting
- ◆ Wall Lamp
- ◆ Road Lighting
- ◆ Parking Lighting
- ◆ AC-LED Lighting

Parameters

Part Number	ZYS-P10A(3 Wires)
Rated working voltage/Un (VAC)	100-277V
Maximum continuous working voltage/MCOV/Uc (VAC) 1	350V
Rated load current/IL(A)	5A
Nominal discharge current/In(kA)2	5KA
Maximum Discharge Current/Imax (kA) 3	10KA
Surge Impulse Voltage/Uoc (KV)	10KV
Voltage Protection Level/Up(V)4	L-N,L-G/PE,N-G/PE≤1.5KV
Power Supply System	TN
Waterproof grade	IP65
Work environment	-40℃~+85℃
UL1449 test classification	Type 5


LED Lighting Surge Protector Datasheet

ZYS-P10A(3 Wires)

Notes:

- 1 Maximum continuous working voltage MCOV/UC(VAC): The maximum continuous working voltage continuously applied to the SPD line end
- 2 Nominal discharge current (In) (kA): The measured value of SPD withstand capability; the measured value of 15 pulses using 8/20us current waveform.
- 3 Maximum discharge current (max) (kA): The maximum discharge current is the measured value of the SPD's maximum withstand capability, and the measured value of 2 pulses using 8/20us current waveform
- 4 Voltage protection level/Up: IEC61643-11 voltage protection level, the maximum residual voltage measured value of the nominal discharge current (In) under continuous application of 8/20u pulses, is the maximum voltage measured value after one round

Dimension



Diagram

