

# T8 LINEAR INTEGRATE

Plastic / Aluminum Material

## BUILDERS PACK

EASY INSTALLATION

### Seamless Linking | Clear Cover

#### DESCRIPTION

LED Integrated Low Bay | Linkable | 50pcs/ctn

Size & Wattage	4ft 40w
CCT	6500K
CRI	82
Beam angle	146°
Warranty	5 years

#### PRODUCT FEATURES

- Max of 600W for linking applications at 120V;  
Max of 1200W for linking applications at 277V
- AC 120-277V
- Seamless linking
- Clear cover
- 50,000+ hour lifetime
- Operating temperature -4°F to +113°F
- ETL Listed
- DLC 5.1 Premium Listed



#### LAMP CODE DEFINITIONS

JL-INT-XFT-ZZW-XXK

JL	INT	XFT	ZZW	XXK
Series	Integrate	Length	Wattage	Color Temperature



**Seamless Linking | Clear Cover****SPECIFICATIONS**

Size	4FT
SKU	53-2611C
Model No.	JL-INT-4FT-40W-65K
Wattage	40W
Efficacy	154.6LPW
Luminous Flux	6118lm
Input Current @120V	330mA
Color Temperature	6500K
Input Voltage	AC120-277V, 50/60Hz
THD	≤20%
Flicker	Flicker
Power Factor	≥0.90
Cover	Frosted
IP Rate	IP20
Working Temperature	-20°C ~ +55°C / -4°F ~ +131°F
Storage Temperature	-40°C ~ +60°C / -40°F ~ +140°F
Lifespan	50,000h

# T8 LINEAR INTEGRATE

Plastic / Aluminum Material

# BUILDERS PACK

EASY INSTALLATION

## Seamless Linking | Clear Cover

### INSTALLATION OF LINKING

Max of 600W for linking applications at 120V, Max of 1200W for linking applications at 277V


Size	Wattage	Linkable Qty @120V PCS	Linkable Qty @277V PCS
4FT	40W	15	30

When you need Integrate Linking in different sizes, please refer to below sheets to ensure the brightness of the maximum approximation

8FT	4FT	3FT	2FT
72W	40W	30W	20W



### PHYSICAL CHARACTERISTICS



Product Size	A (Body Length)	B (Width)	C (Height)
4FT	45''	1.18''	1.42''

## Seamless Linking | Clear Cover

### ACCESSORIES (purchased separately)

#### -Mounting Accessory



6ft On/Off Cable

SKU# 53-26W



Magnet Clips

SKU# 53-26M



Mounting Clips

SKU# 53-263



Single-end Cable

SKU# 53-264



Double-end Cable

SKU# 53-265



Butt Connector

SKU# 53-266

#### -480V to 277V Step-Down Non-Isolated Auto-Transformers



Builderspack's 480V to 277V Step-Down Auto-Transformers are designed to step down 480V to 277V single-phase power.

These transformers enable consumers to utilize common universal voltage (120-277V) LED fixture in applications where the main facility power is 480V.

### Seamless Linking | Clear Cover

**PAGKAGE**

SKU	SIZE	Length	Width	Height	Pcs / Carton	Net Weight	Gross Weight
53-2611C	4FT	46.46"	15.16"	9.25"	50 pcs	0.75lbs	45.99lbs

**PALLET & CONTAINER LOADING**

SKU	Size	Length	Width	Height	Gross Weight	40' HQ Loading Qty
53-2611C	4FT	48"	40.55"	78.74"	893.81lbs	30,000pcs

