

# T8 LINEAR INTEGRATE

Plastic / Aluminum Material

**BUILDERS PACK**  
EASY INSTALLATION

## Seamless Linking | Clear Cover

### DESCRIPTION

LED Integrated Low Bay | Linkable | 20pcs/ctn

Size & Wattage	8ft 72w
CCT	6500K
CRI	82
Beam angle	146°
Warranty	5 years

### PRODUCT FEATURES

- Max of 600W for linking applications at 120V;  
Max of 1200W for linking applications at 277V
- AC 120-277V
- Seamless linking
- Clear cover
- 50,000+ hour lifetime
- Operating temperature -4°F to +113°F
- ETL Listed
- DLC 5.1 Premium Listed



### LAMP CODE DEFINITIONS

**JL-INT-XFT-ZZW-XXK**

JL	INT	XFT	ZZW	XXK
Series	Integrate	Length	Wattage	Color Temperature



### Seamless Linking | Clear Cover

#### SPECIFICATIONS

Size	8FT
SKU	53-2612C
Model No.	JL-INT-8FT-72W-65K
Wattage	72W
Efficacy	153.3LPW
Luminous Flux	11194lm
Input Current @120V	600mA
Color Temperature	6500K
Input Voltage	AC120-277V, 50/60Hz
THD	≤20%
Flicker	Flicker
Power Factor	≥0.90
Cover	Frosted
IP Rate	IP20
Working Temperature	-20°C ~ +55°C / -4°F ~ +131°F
Storage Temperature	-40°C ~ +60°C / -40°F ~ +140°F
Lifespan	50,000h

# T8 LINEAR INTEGRATE

Plastic / Aluminum Material

**BUILDERS PACK**  
EASY INSTALLATION

## Seamless Linking | Clear Cover

### INSTALLATION OF LINKING

Max of 600W for linking applications at 120V, Max of 1200W for linking applications at 277V


Size	Wattage	Linkable Qty @120V PCS	Linkable Qty @277V PCS
8FT	72W	8	16
4FT	40W	15	30
3FT	30W	20	40
2FT	20W	30	60

When you need **Integrate Linking** in different sizes, please refer to below sheets to ensure the brightness of the maximum approximation

8FT	4FT	3FT	2FT
72W	40W	30W	20W



### PHYSICAL CHARACTERISTICS



Product Size	A (Body Length)	B (Width)	C (Height)
8FT	90''	1.18''	1.42''

**Seamless Linking | Clear Cover**


ACCESSORIES (purchased separately)

**-Mounting Accessory**

		
<p>6ft On/Off Cable SKU# 53-26W</p>	<p>Magnet Clips SKU# 53-26M</p>	<p>Mounting Clips SKU# 53-263</p>

		
<p>Single-end Cable SKU# 53-264</p>	<p>Double-end Cable SKU# 53-265</p>	<p>Butt Connector SKU# 53-266</p>

**-480V to 277V Step-Down Non-Isolated Auto-Transformers**

	<p>Builderspack’s 480V to 277V Step-Down Auto-Transformers are designed to step down 480V to 277V single-phase power. These transformers enable consumers to utilize common universal voltage (120-277V) LED fixture in applications where the main facility power is 480V.</p>
---	---

### Seamless Linking | Clear Cover

#### PAGKAGE

SKU	SIZE	Length	Width	Height	Pcs / Carton	Net Weight	Gross Weight
53-2612C	8FT	91.34''	7.91''	7.48''	20 pcs	1.41lbs	33.97lbs

#### PALLET & CONTAINER LOADING

SKU	Size	Length	Width	Height	Gross Weight	40' HQ Loading Qty
53-2612C	8FT	Customized extra-long pallets				15,000pcs