



### **DESCRIPTION**

Plastic / Aluminum |8FT| Type B |25pcs/ctn

Wattage	40w
ССТ	5000K
CRI	82
Beam angle	146°
Warranty	5 years



### **PRODUCT FETURES**

- Bypass ballast runs on 120-277V line voltage
- Frosted cover
- Single- or double-ended wiring
- 50,000+ hour lifetime
- Suitable for dry and damp indoor locations
- Operating temperature -4°F to +113°F
- ETL Listed
- DLC 5.1









### LAMP CODE DEFINITIONS

### JL-ALT8-8FTB-ZZW-CCT













- 1 JL = Factory Code
- (2) ALT8 = Plastic / Aluminum T8 tubes
- (3) 8FT = Fixture Length 8ft
- (4) B = TYPE B
- (5) ZZW = Wattage
- 6 CCT = Color Temperature






### **SPECIFICATIONS**

SKU	53-1844-50
Model No.	JL-ALT8-8FTB-ZZW-CCT
Wattage	40W
Efficacy	149.6LPW
Luminous Flux	5356lm ± 5%
Input Current @120V	300mA
Color Temperature	5000K
Input Voltage	AC120-277V, 50/60Hz
THD	≤20%
Flicker	Flicker
Power Factor	≥0.95
Wire Connection	Single- or Double-Ended Wiring
Cover	Frosted
IP Rate	IP20
Working Temperature	-20°C ~ +55°C / -4°F ~ +131°F
Storage Temperature	-40°C ~ +60°C / -40°F ~ +140°F
Lifespan	50000h


#### **DISTRIBUTION CURVE**








### **DISTANCE CURVE**





#### INSTALLATION INSTRUCTIONS


BY-PASS REPLACEMENT (WITHOUT BALLAST)


- 1. Disconnect power from fixture.
- 2. Remove fluorescent lamps.
- 3. Remove lens and wiring compartment, if applicable.
- 4. Cut all wires connected to ballast (see Figure A: Typical Ballast Configurations).

















### **PHYSICAL CHARACTERISTICS**





## Lamp Dimensions

A (Body Length)	92.78"		
B (Illuminated Length)	91.08"		
C (Width)	1.32"		
D (Height)	1.15"		

### **PACKAGE**

Product Size	Pcs / Carton	Length	Width	Height	Gross Weight	Net Weight
8ft	25 pcs	95.28"	7.28''	6.30''	25.68lbs	1.1lbs

