



### **DESCRIPTION**

Plastic / Aluminum |8FT| Type B |25pcs/ctn

Wattage	50w
ССТ	6500K
CRI	82
Beam angle	146°
Warranty	5 years



### **PRODUCT FETURES**

- Bypass ballast runs on 120-277V line voltage
- Clear cover
- Single- or double-ended wiring
- 50,000+ hour lifetime
- Suitable for dry and damp indoor locations
- Operating temperature -4°F to +113°F
- ETL Listed
- DLC 5.1









### LAMP CODE DEFINITIONS

### JL-ALT8-8FTB-ZZW-CCT













- 1 JL = Factory Code
- (2) ALT8 = Plastic / Aluminum T8 tubes
- (3) 8FT = Fixture Length 8ft
- (4) B = TYPE B
- (5) ZZW = Wattage
- 6 CCT = Color Temperature






### **SPECIFICATIONS**

SKU	53-1845-65				
Model No.	JL-ALT8-8FTB-ZZW-CCT				
Wattage	50W				
Efficacy	151.3LPW				
Luminous Flux	7252lm ± 5%				
Input Current @120V	438.6mA 6500K AC120-277V, 50/60Hz				
Color Temperature					
Input Voltage					
THD	≤20%				
Flicker	Flicker				
Power Factor	≥0.95				
Wire Connection	Single- or Double-Ended Wiring				
Cover	Clear				
IP Rate	IP20				
Working Temperature	-20°C ~ +55°C / -4°F ~ +131°F				
Storage Temperature	-40°C ~ +60°C / -40°F ~ +140°F				
Lifespan	50000h				


#### **DISTRIBUTION CURVE**








### **DISTANCE CURVE**





#### INSTALLATION INSTRUCTIONS


BY-PASS REPLACEMENT (WITHOUT BALLAST)


- 1. Disconnect power from fixture.
- 2. Remove fluorescent lamps.
- 3. Remove lens and wiring compartment, if applicable.
- 4. Cut all wires connected to ballast (see Figure A: Typical Ballast Configurations).

















### **PHYSICAL CHARACTERISTICS**





### **Lamp Dimensions**

A (Body Length)	92.78"
B (Illuminated Length)	91.08"
C (Width)	1.32"
D (Height)	1.15"

### **PACKAGE**

Product Size	Pcs / Carton	Length	Width	Height	Gross Weight	Net Weight
8ft	25 pcs	95.28"	7.28"	6.30"	25.68lbs	1.1lbs

