

5 YEAR WARRANTY

EXTENDED WARRANTY AVAILABLE

50,000 LIFETIME HOURS

UL CERTIFIED, DLC PREMIUM RATED

FEATURES & HIGHLIGHTS

UL# **E491628**

High Output

Small Form Factor

Traditional Design Non-Intrusive



APPLICATIONS

Manufacturing

Factory

Warehouse

Gymnasium



SKU	Lamp Code	Size	Wattage	Equivalency	CCT	Efficiency	Lumens	CRI
GL20001-1	33-LH-12-7105-840-D-S	1'x2'Ft	105w	4 x 54W T5HO	4000k	130.37 lm/w	13976 lm	>80
GL20001-2	33-LH-12-7105-850-D-S				5000k	131.21 lm/w	14131 lm	>80
GL20002-1	33-LH-12-7165-840-D-S	1'x2'Ft	165w	6 x 54W T5HO	4000k	132.68 lm/w	21786 lm	>80
GL20002-2	33-LH-12-7165-850-D-S				5000k	133.58 lm/w	22027 lm	>80
GL20003-1	33-LH-14-7220-840-D-S	1'x4'Ft	220w	8 x 54W T5HO	4000k	130.48 lm/w	28092 lm	>80
GL20003-2	33-LH-14-7220-850-D-S				5000k	133.54 lm/w	29378 lm	>80

CHARACTERISTICS (SHARED)

BRAND	GLLUSA
Beam Angle	115°
L70 Lumen Maintenance (Hours)	50,000
Power Factor	>0.9
Input Voltage	AC 100-277v
Dimmable	Yes 0-10v
Frequency	50/60Hz
Operating Temperature	-20°C ~ +40°C
IP Rating	IP20
Certification(s)	UL, DLC, cUL, RoHS
Environment	Indoor

AVAILABLE ACCESSORIES


Standard	Hanging chains
GL52044	Microwave Motion Sensor

MODEL SETUP

Internal Use	Category	Size/Length	Watts	CCT	Dimmable	Other
33	LH = Linear High Bay	12 = 1'x2'Ft 14 = 1'x4'Ft	7105 = 105w	840 = 4000k	D = 0-10v	S = Sensor

PRODUCT DIMENSIONS

Product	A	B	C	Net Weight
105w	23.62"	12.6"	3.54"	3.8 kg / 8.36 lbs
165w	23.62"	17.32"	3.54"	5.9 kg / 12.98 lbs
220w	45.94"	12.6"	3.54"	6.3 kg / 13.86 lbs



SHIPPING INFORMATION

Product	Master Carton & Weight	Pcs/Carton	Pcs/Pallet	Pcs/20'GP	Pcs/40'GP	Pcs/40'HQ	Pcs/45'GP
105w	25.6"x14.6"x8.9" & 21.2 lbs	2	64	768	1600	1728	2120
165w	25.6"x19.3"x8.9" & 28.2 lbs	2	38	512	1000	1152	1380
220w	47.8"x14.6"x8.9" & 36.7 lbs	2	32	384	780	864	1100

Note: All container quantities are palletized.