



WATTAGE SELECTION LED HIGHBAY

FEATURES

- Die formed galvanized steel, white pain
- High efficacy meet premium;
- Isolated driver with wide voltage input option
- Accessories available for hanging, and pendant mount
- Accessories available for hanging, surface mounting;
- Various emergency backup and sensor options
- 5 Year warranty

APPLICATIONS

- Warehouses;
- Manufacturing facilities;
- Gymnasiums;
- Commercial facilities;



ORDERING INFORMATION

Example: EVL-ELHB2-110/135/160/D10/U/50

Name	Length	Wattage	Dim	Driver	Color Temp.	Backup	Sensor
ELHB	2:2ft	-70/90/110	/D10	/U:120-277V	/40:4000K	Blank: None	Blank: None
		-110/135/160					
		-180/200/220			/50: 5000K	/EM: Emergency	/MS: Motion
	4:4ft	-180/200/220				Battery	Sensor
		-240/280/320				Backup	
		-340/380/420					

2ft ELHB wattage selectable 110/135/160W 120-277V 5000K

SPECIFICATIONS



EVERLUX LED INC

79 EMJAY BLVD, BRENTWOOD, NY 11717 TEL: 631-522 1628

Model	ELHB2		ELHB4	
Wattage	Field adjustable	Field adjustable	Field adjustable	Field adjustable
	70/90/110W	180/200/220W	180/200/220W	340/380/420W
	110/135/160W		240/280/320W	
Voltage	120-277V	120-277V	120-277V	120-277V
LM/W	135			
CCT	5000K			
CRI	>80			
L70/L90	>100,000h / >40,000h			
Dimension(mm)	625*320*92mm	625*440*92mm	1200*320*92mm	1200*440*92mm

Note: Actual performance may differ as a result of end-user environment and application.


PHOTOMETRIC DATA




ACCESSORIES



V-Hook & Chain



Pendent Mount kit



Emergency Battery Pack



Sensor